











MADE IN FRANCE

BDR 2400 U/R

APPLICATION SPECIALTIES



CABLES



ALLIMINIIM SCRAPS



WEE



ACSR



TIRES



CU / AL RADIATORS



BDR 2400 U / BDR 2400 R





- → 5 t disengageable flywheel
- 120 t of torque at blade tip
- Easy handling of sticking points



FLYWHEEL

→ Friction disc / clutch

POTENZA	300 HP / 220 Kw	375 HP / 280 Kw
PESO	27 T	30 T
VELOCITA DI TAGLIO	110 - 145 RPM	110 - 125 RPM

ROTOR

→ Length: 2400 / 2400 mm (94.4 INCH)

LOW SPEED FOR HIGHER TORQUE

→ A more powerful shredder

ROTATING SENSORS

Protects the belt and transmission in case of jamming

RECTANGULAR **BLADES**

28 X 56 X 195 MM

→ Reversible 4 times

Easily accessible blade gapping system

→ Proprietary steel alloy





MOBILE BLADES

36

FIXED BLADES

12

SCREENS FROM 10 MM TO 75 MM

EASY MAINTENANCE

- → Easy screen replacement thanks to hydraulic assistance
- → Easy access for maintenance
- → User friendly

OUR PREMIUM SERVICES

- · Customized engineering
- · Experience from being operator
- · On-site installation and commissioning
- · Training on both operation and crane feeding
- Ultra-responsive customer service





